

Extinction ratio of germanium-silicon modulators





Extinction ratio of germanium-silicon modulators

Review of Silicon Photonics Technology and Platform Development

To integrate such PIN photodetectors into the silicon photonics platform, the hetero-epitaxial germanium (Ge) is generally considered to be the ideal intrinsic region material as it has strong absorption in the

[Read More](#)

On-chip silicon electro-optical modulator with ultra-high extinction

Here, the authors demonstrate an ultra-high extinction ratio electro-optical modulator on silicon and its application for DAS.

[Read More](#)



(PDF) Germanium electro-absorption modulator for power efficient

We report a novel evanescent-coupled germanium electro-absorption modulator with a small active area of $16 \mu\text{m}^2$ giving an extinction ratio of ~ 10 dB for a wavelength range of 1580 -

[Read More](#)

Silicon Mach-Zehnder modulator of extinction ratio

Silicon Mach-Zehnder modulators with reduced series resistance in lateral PN junction rib-waveguide phase shifters for enhanced high-speed

[Read More](#)

High-speed germanium-based waveguide electro-absorption modulator



Germanium-based waveguide electro-absorption modulators are reported in C- and L-band wavelength operation at 56Gb/s (NRZ-OOK) with extinction ratio of >3dB at 2V peak-to-peak and insertion loss

[Read More](#)

Understanding the Dynamic and Static Extinction Ratios

Explore the differences between static and dynamic extinction ratios in Ge electro-absorption modulators (EAMs). Learn how optical input power and self-heating

[Read More](#)

(PDF) Hybrid Silicon and Lithium Niobate Modulator

Hybrid Silicon and Lithium Niobate Modulator Shihao Sun, Mingbo He, Mengyue Xu, Shengqian Gao, Siyuan Yu, and Xinlun Cai (Invited Paper)

[Read More](#)



On the dynamic and static extinction ratio of germanium electro

We compare dynamic and static extinction ratios of germanium electro-absorption modulators (EAM) and their dependency on optical power. We discuss that the common figure of merit, the quotient of

[Read More](#)

Slow-light silicon modulator with 110-GHz bandwidth

Design of slow-light silicon modulator with ultrahigh bandwidth and compact size. (A) The detailed device geometry and doping configuration of the

[Read More](#)

Calculating modulation response

In this document, we will describe the procedure for determining the modulation



response using the effective index of the waveguide. The effective index can be

[Read More](#)

64 Gb/s O-Band GeSi Quantum-Confined Stark Effect Electro

A wafer-scale analysis of static insertion loss (IL) and extinction ratio (ER) is presented, showing IL down to 7.5 dB with ER of 5 dB for a 36.8 μm long device, at drive voltages of 2 V peak-to-peak.

[Read More](#)

Extremely high extinction ratio electro-optic modulator via frequency

In particular, they are required for the control and manipulation of atomic systems such as atomic clocks and quantum computers. Typical integrated electro-optic modulators operating at

[Read More](#)



Effect of Germanium Doping on the Performance of a Silicon Optical

In this paper, the transfer characteristics of a germanium doped silicon Mach-Zehnder modulator (MZM) have been plotted and compared with a silicon MZM. The germanium doped silicon MZM can

[Read More](#)

Design and fabrication of a novel evanescent germanium electro

An electro-absorption (EA) modulator holds distinct advantages over the silicon Mach-Zehnder interferometer (MZI) modulator by having lower energy consumption, a smaller footprint on

[Read More](#)

OpenLight and Tower Semiconductor Demonstrate



Home » Press Releases OpenLight and Tower Semiconductor Demonstrate 400G/lane Modulators Built on Silicon Photonic Wafers for Data

[Read More](#)

Compact, High Extinction Ratio Silicon Mach-Zehnder Modulator with

An integrated silicon photonic MZM modulator with a slow-wave architecture to reduce V_πL is presented. This structure achieves an 80% enhancement in extinction ratio and has a 14GHz

[Read More](#)

Monolithic electro-optic platform on silicon with bandwidth of

We demonstrate a scalable C-band silicon photonic platform monolithically integrating ultra-high speed germanium-silicon electro absorption modulators and fin photodiodes.

[Read More](#)



Compact, High Extinction Ratio Silicon Mach-Zehnder Modulator with

Compact, High Extinction Ratio Silicon Mach-Zehnder Modulator with Corrugated Waveguides Reza Hosseini^{1*}, Aroutin Khachaturian², Mircea Catuneanu¹, Parham Porsandeh Khial², Reza Fatemi²,

[Read More](#)

10 Gbit/s Silicon modulator and germanium detector chip-to

Experimental results of a high-speed silicon optical modulator based on carrier depletion in a p-p-n diode and Germanium photodetectors are presented. 10 Gbit/s data transmission is obtained

[Read More](#)

On the dynamic and static extinction ratio of germanium electro



We have found that the extinction ratio (ER) of an electroabsorption modulator integrated with a distributed feedback laser strongly depends on the incident power to the modulator.

[Read More](#)

(a) Measured extinction ratio and insertion loss of a Ge

We present the design and fabrication of a waveguide-based Ge electro-absorption (EA) modulator integrated with a 3 μm silicon-on-insulator (SOI) waveguide. The

[Read More](#)

Understanding the Dynamic and Static Extinction Ratios

Introduction Germanium electro-absorption modulators (Ge EAMs) are promising candidates for energy-efficient and high-speed optical transmitters in silicon

[Read More](#)



Improved extinction ratio of Mach-Zehnder based optical modulators

Silicon based optical modulators with improved extinction ratio (ER) of 25 dB were demonstrated on complementary metal oxide semiconductor (CMOS) platform. It was proposed that

[Read More](#)

Thermo-Optical Analysis of O-Band GeSi Quantum Confined Stark

The optimum extinction ratio (ER) undergoes a red shift and is preserved at higher temperatures. The self-heating of the device due to optical absorption is assessed using finite element (FE) simulations,

[Read More](#)

PCM3_R1



Using a PCM with higher refractive index change upon phase-transition and lower extinction coefficient can increase the turnability of the designed filter. However, this would decrease

[Read More](#)

Design and analysis of graphene slot waveguide micro-ring modulator

Highlights o The paper introduced a novel design of a graphene ring modulator that balances the trade off between extinction ratio and bandwidth. o The research demonstrates that the

[Read More](#)

Conference title, upper and lower case, bolded, 18 point type, centered

We performed a detailed reliability study of GeSi Electro-Absorption Modulators integrated in a silicon photonics platform using a wide range of stress and performance parameters.



[Read More](#)

Contact Us

For datasheets, pricing, or custom data center infrastructure solutions, please visit:
<https://www.zeldaterblanchephotography.co.za>